

IMPRESSIONS™ CLIMAPLUS™



Impressions Panels with ClimaPlus Performance /
DONN Centricitee DXT Suspension System

FEATURES AND BENEFITS

- Micro fissured non-directional pattern for a cleaner, whiter appearance
- ClimaPlus 30-year lifetime system warranty to withstand temperature and humidity conditions up to 49°C (120°F)/99% relative humidity without visible sag when used with a DONN® Brand suspension system.


APPLICATIONS

- Offices
- Retail
- Warehouse
- Schools
- Showrooms
- Restaurants








SUBSTRATE

- Water-felted mineral-fiber

Medium-textured panel



IMPRESSIONS
CLIMAPLUS PANELS

Edge	Panel Size ²	Class	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹
SQ 	2 x 2 x 5/8" 600 x 600 x 16mm	Class A	903 ME903	.60	33	.84	White	A, B	Low		45%
	2 x 4 x 5/8" 600 x 1200 x 16mm	Class A	904 ME904	.60	35	.84	White	A	Low		45%
SLT 	2 x 2 x 5/8" 600 x 600 x 16mm	Class A	905 ME905	.60	33	.84	White	C	Low		45%
	2 x 4 x 5/8" 600 x 1200 x 16mm	Class A	908 ME908	.60	35	.84	White	C	Low		45%
FLB 	2 x 2 x 5/8" 600 x 600 x 16mm	Class A	916 ME916	.60	33	.84	White	D	Low		45%
	2 x 4 x 5/8" 600 x 1200 x 16mm	Class A	911 ME911	.60	35	.84	White	D	Low		45%

LEGEND






 Low Emission (VOC Class)

Meets the emission test criteria as low-emitting prescribed by the Singapore Green Building Council (SGBC) following ASTM D5116-06 testing methods.

 ClimaPlus Superior Performance

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew.

GRID PROFILE
OPTIONS

A DX® DXI DXII DXIII	B Centricitee™ DXT™	C DX®	D Centricitee™ DXT™	E Fineline® 1/4" DXF™
				

Short Specification:

- Ceiling system shall comprise USG Impressions ClimaPlus™ high humidity / fire resistant acoustical ceiling panels in (DONN Centricitee 15mm [9/16"] / DONN DX 24mm [15/16"] Fineline 15mm [9/16"] exposed grid including wall trim as manufactured by USG Boral.
- Panels shall have NRC 0.55.
- Panels shall have CAC 33-35.
- Nominal size (600mm x 600mm / 600mm x 1200mm) x 16mm / (2' x 2' / 2' x 4') x 5/8".
- Edge detail shall be (Fineline Bevel [FLB] / Shadowline Tapered [SLT] / Square [SQ]).
- Limiting Conditions - Maximum 49°C (120°F)/99% RH.

PHYSICAL DATA/
FOOTNOTES

Weight
3.86-4.23 kg/2'

Thermal Resistance
R 0.3

Environmental Limitations
49°C, 99% RH max.

Maximum Backloading
0kg/m²

Reaction to Fire

Standard	Flame Spread	Smoke Developed
ASTM E84	<25	<50
AS/NZS 3837	Group Number Classification: 1 unsprinklered	
ISO 5860 Parts 1 & 2	Group Number Classification: 1 - S	

Maintenance

Can be cleaned easily with a soft brush or vacuum. To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface.



Available From

0800 POTTERS
www.potters.co.nz // info@potters.co.nz

Manufactured, sold or distributed by USG Boral Building Products or one or more of its affiliates.

The trademarks CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXT, FINELINE, IMPRESSIONS are trademarks of USG Boral Building Products or one or more of its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

